



产品说明书 Technical Datasheet

&\$%

AUhYf]U` HndY DD5Z;:' \$; fUXY BUaY DD5 L*H &&' \$! : F6
: YUhi fYg	6fca] bY Z` UaY fYhUfXUbh ; ccX ac` X] b[UbX dfcWgg] b[dYfZcfaUbW <] [\ ghfYb[h\
AUhYf]U` GhUbXUfX	
5j U]` UV]` hm	5g] Ub! DUW]Z] W
DfcWgg AYh\cX	=b^YVh] cb Ac` X] b[
5ddYUfUbW	7c` cf g Cdh] cbU
5dd`] WUh] cbg	5i hcacV]` Y 9 YVhf] WJ` #9 YVhf] cb] W 5dd`] WUh] cbg

; YbYfU` DfcdYfh] Yg

Bc"	DfcdYfh] Yg	AYh\cXg	I b] hg	JU` i Yg	HYgh 7cbX] h] cbg
%	8Ybg] hm	=GC %% ' ! %	[#VhR	%) -	&
&	: `ck Ac` X] b[g\ f] b_U[Y	DF9H	!	\$" &	&
'	HfUbg] YfgY Ac` X] b[g\ f] b_U[Y	DF9H	!	\$" ,	&
(HYbg]` Y GhfYb[h\ Uh AU! @cUX	=GC)&+! &	ADU	%+\$) \$aa#a] b
)	9 cb[Uh] cb Uh 6fYU_	=GC)&+! &	i	%) r' " \$) \$aa#a] b
*	: `YI i fU` GhfYb[h\	=GC %+,	ADU	& \$	&aa#a] b
+	: `YI i fU` AcXi` i g	=GC %+,	ADU	%&) \$\$	&aa#a] b
,	=adUW^ GhfYb[h\	=GC %+-! %	_>#aR&	()	&
-	BchVXYX =adUW^ GhfYb[h\	=GC %+-! %	_>#aR&	-	&
%\$: `UaaUV]`] hm	I @ (!	J! \$	% *aa

DfcWgg] b[VtbX] h] cbg

8fm] b[7cbX"	%) r%&) + *r%&\
Ac] ghi fY 7cbhfc`	\$" &
=b^YVh] cb HYad"	&- \$! ' &\$
Ac` X HYad"	%&\$r % \$

注：以上数据为实验典型值，真实可靠，仅作参考，不能认定为材料性能最小值。

Note: The technical data above are authentic and reliable for reference. These value cannot be defined as the minimal performance value.